BagIt Summary Page 1 of 2

PREPARATION to run the Bagit bag command

Open a DOS Command Window (Start -> Run. Then enter: cmd)

view JAVA_HOME environmental variable setting (assumes JRE installed on C: drive)

(You can check the Java entry in the Control Panel to see where your JRE is installed)

> set

JAVA HOME=C:\Program Files\Java\jre6

Assumes BagIt application is installed on Portable Drive connected at E:

\ F

> cd \bagit-3.9\bin

> dir

bag

bag.bat

CREATING A BAG

1a. create a Bag containing one folder:

> bag create E:\BagIt_Bags\my_1999_NC_Congress_Districts_bag H:\GIS_datasets\1999_NC_Congress_Districts list of files to put in bag

** use _bag suffix to denote that this is a bag

1b. create a Bag containing several folders

> bag create E:\BagIt_Bags\my_NC_Congress_Districts _bag H:\ GIS_datasets\1992_NC_Congress_Districts H:\ GIS_datasets\2009_NC_Congress_Districts

2. To verify a Bag:

> bag verifyvalid E:\BagIt Bags\my 1999_NC Congress Districts_bag

name of bag to verify/validate

Result is True - means that the bag is valid

Result is False - means that something in the bag is altered. Read message for more information

RETRIEVING, VERIFYING, UNPACKING A BAG

- 1. Copy bag from the Portable Disk Device to a local "staging" folder (e.g. H:\BagIt_Staging)
- 2. Verify the bag has arrived intact and unaltered
- > bag verifyvalid H:\BagIt_Staging\my_1999_NC_Congress_Districts_bag

name of bag to verify/validate

Result is True - means that the bag is valid

Result is False - means that something in the bag is altered. Read message for more information

- 3. Navigate down into H:\BagIt_Staging\my_1999_NC_Congress_Districts_bag\data
- 4. Use Windows Explorer to copy the files out of the bag into your local working space from the data folder

BagIt INFORMATION FILES

bag-info.txt - records # of files in the bag, the date the bag was created, the disk utilization size for the bag manifest-md5.txt - records the list of all files put inti the bag and the checksum for each of the files (see data dir) tagmanifest-md5.txt - records the list of all of the bag information files and the checksum for each info file

BagIt Summary Page 2 of 2

Installation Sites:

Java Runtime Environment:

http://www.oracle.com/technetwork/java/javase/downloads/index.html

Select: **Download JRE**

Must install Java Runtime Environment on your computer, and then set the JAVA_HOME environmental variable. (Setting the JAVA_HOME environmental variable generallyl requires Administrator's rights)

BagIt:

http://sourceforge.net/projects/loc-xferutils/

Select: **Download bagit-3.9-bin.zip**

Download the compiled binary that's available, rather than the source code.

Installation consists of a simple copy of the bagit-3.9 folder from the zip archive into your folder structure. Recommend placing near top of the directory hierarcy, as you will need to 'cd' to this directory to invoke the bag command through a DOS command window (see page 1)